

Reference Sheet of Standard Metric Sizes & Shapes

<p>1. STANDARD</p> <p>SIZE CODE 5</p>	<p>2. STANDARD NOTE 1</p> <p>SIZE CODE 10 - 15</p>	<p>3. STANDARD NOTE 1</p> <p>SIZE CODE 20 - 25 - 30</p>	<p>4. PIER</p> <p>SIZE CODE 20 - 25 - 30</p>	<p>5. BREAKER NOTE 2</p> <p>SIZE CODE 10 - 15 - 20 - 30</p>
<p>6. ASHLAR STANDARD NOTE 1, 2</p> <p>SIZE CODE 10 - 15</p>	<p>7. ASHLAR STANDARD NOTE 1, 2</p> <p>SIZE CODE 20 - 25 - 30</p>	<p>8. PIER HALF</p> <p>SIZE CODE 15 - 20 - 25 - 30</p>	<p>9. BULLNOSE L/CORNER</p> <p>SIZE CODE 10 - 15</p>	<p>10. RETURN CORNER</p> <p>SIZE CODE 10 - 15</p>
<p>11. RETURN CORNER</p> <p>SIZE CODE 25 - 30</p>	<p>12. 75% SOLID STANDARD NOTE 3</p> <p>SIZE CODE 10 - 15</p>	<p>13. 75% SOLID STANDARD NOTE 2, 3</p> <p>SIZE CODE 20 - 25 - 30</p>	<p>14. SOLID STANDARD NOTE 2</p> <p>SIZE CODE 20 - 25 - 30</p>	<p>15. SOLID PIER</p> <p>SIZE CODE 10 - 15 - 20 - 25 - 30</p>
<p>16. CAP (SEMI SOLID)</p> <p>SIZE CODE 20 - 25 - 30</p>	<p>17. SINGLE BULLNOSE NOTE 1, 2</p> <p>SIZE CODE 10 - 15 - 20 - 25 - 30</p>	<p>18. DBL. BULLNOSE END NOTE 1, 2</p> <p>SIZE CODE 10 - 15 - 20 - 25 - 30</p>	<p>19. DBL. BULLNOSE FACE NOTE 1, 2</p> <p>SIZE CODE 20 - 25</p>	<p>20. 1/2 SINGLE BULLNOSE</p> <p>SIZE CODE 10 - 15 - 20 - 25 - 30</p>
<p>21. 1/2 DBL. BULLNOSE</p> <p>SIZE CODE 15 - 20 - 25 - 30</p>	<p>22. W - BLOCK</p> <p>SIZE CODE 20</p>	<p>23. UNIVERSAL KNOCKOUT</p> <p>SIZE CODE 15 - 20 - 25 - 30</p>	<p>24. BOND BEAM</p> <p>SIZE CODE 25 - 30</p>	<p>25. BOND BEAM</p> <p>SIZE CODE 15 - 20</p>
<p>26. 30x30 BULLNOSE PIER</p>		<p>27. CHIMNEY BLOCK NOTE 5</p>	<p>28. CHIMNEY BLOCK NOTE 5</p>	<p>29. CONCRETE BLOCK</p> <p>SIZE CODE 5</p>

1-800-487-370 | www.simcoesolutions.com

NOTES

- NOTE 1 MAY BE SUPPLIED WITH BREAKER.
- NOTE 2 END CONFIGURATION MAY VARY.
- NOTE 3 MEETS ONTARIO BUILDING CODE REQUIREMENTS OF SOLID MASONRY UNITS
- NOTE 4 OUTSIDE DIMENSIONS MAY VARY
- NOTE 5 AVAILABLE WITH CUT-OUT

NOMINAL METRIC SIZE CODE	REPLACES IMPERIAL SIZE CODE	DIMENSION "A" ACTUAL MEASUREMENT
5	2"	40 mm
10	4"	90 mm
15	6"	140 mm
20	8"	190 mm
25	10"	240 mm
30	12"	290 mm